



Product Specification

Flowserve Corporation Flow Control Division www.flowserve.com 1350 N. Mountain Springs Parkway Springville, Utah 84663-3004 Phone: 801 489 2233 1978 Foreman Dr. Cookeville, TN 38501 Phone: 931 432 4021

Logix Digital Positioner Accessories

SoftTools Software

Our SoftTools software package provides all tools necessary to establish communications with your Logix positioner using a personal computer via the HART protocol. The SoftTools software suite provides intuitive graphic screens for configuring the positioner with special emphasis on limits and alarms, internal PID loop tuning for dynamic performance optimization and custom valve characterization. SoftTools is also used to view alarm conditions and enter electronic valve data stored in the Logix positioner's on-board memory.

SoftTools Version 7.0 introduces the most advanced and comprehensive set of valve and positioner diagnostics available today. The SoftTools Suite now consists of three separate editions as follows:

SoftTools Suite LE (Lite Edition)
SoftTools Suite SE (Standard Edition)
SoftTools Suite ME (MUX Edition)

How to Order: contact Flowserve representative @ (801) 489-2679 for SoftTools suite licenses and CDs.



Automax Valve Automation Systems



Product Specification

Flowserve Corporation Flow Control Division www.flowserve.com 1350 N. Mountain Springs Parkway Springville, Utah 84663-3004 Phone: 801 489 2233 1978 Foreman Dr. Cookeville, TN 38501 Phone: 931 432 4021

HART Modems

The RS232 cable modem allows easy connection between your Logix positioner and personal computer. It plugs into your computer's serial port and has two mini-grab terminals for direct connection to the Logix test loops. The modem's six-foot cable permits flexibility in field configuring your positioner.

How to Order: Specify part number 10078999

A PCMCIA modem (not shown) is also available for direct installation in your laptop. It features mini-grab terminals for direct connection to the Logix test loops.

How to Order: Specify part number 10079000



HART Filter

The HART Filter may be used to prevent HART modulation from reaching your PLC, controller, or computer's 4-20 mA output port. Some controlling devices interpret the HART modulation as noise, resulting in compromised valve position accuracy.

How to Order: Specify part number 10079944

Rosemount 375 HART Communicator

The Rosemount 375 HART Communicator (not shown) provides hand-held access to the Logix positioner. Pre-loaded with the Logix 3200IQ and 520si device descriptions, the 375 permits configuration of most Logix parameters.

How to Order: Specify part number 10076796

