



# Valtek<sup>®</sup> Mark One<sup>™</sup> Control Valve Quick-Ship Program

**Engineered control valves  
in one week or less**



During routine maintenance and emergency repairs, speed is everything. For every hour of downtime, an operation can lose millions in revenue. Getting replacement valves quickly could mean sacrificing quality for speed. But that's not the case with our Valtek Mark One Control Valve Quick-Ship Program.

With the Valtek Mark One Control Valve Quick-Ship Program, you'll receive quality, Flowserve-tested Mark One valves anywhere in North America in one week or less, and in many cases, we can deliver valves within 24 to 48 hours, so you can reduce downtime and keep your operation moving. In contrast, standard industry lead times for valves can be anywhere from four to 12 weeks.

## Customer benefits:

### **Reduce maintenance-related downtime.**

While valve delivery timelines vary depending on your specific application, configuration and geographic location, Flowserve typically can size, select, build, test and ship standard Mark One control valve configurations in one week or less, minimizing downtime and allowing faster return to operations.

### **Have confidence that you're receiving high-quality control valves.**

With the Valtek Mark One Control Valve Quick-Ship Program, you'll have confidence that you're getting a quality, Flowserve-tested valve. All valves supplied under the program undergo seat leakage testing as per applicable ANSI standards and a detailed and documented ISO:9001 final inspection. Mark One control valve hydrotesting is available with short lead times.

### **Superior performance.**

Valtek Mark One globe control valves offer superior performance in liquid and gaseous services, while also enabling easy, fast and inexpensive maintenance. The spring cylinder-actuated Mark One valve combined with the Logix<sup>™</sup> 3220 digital positioner provides stiffness and maintains high positioning accuracy, repeatability, controlled high speed and dependable response.

## Product specifications:

- Body style: globe
- Temperatures: -30°C to 400°C (-20°F to 750°F)
- NPS sizes: 0.5 to 6
- Pressure classes: 150 to 600
- Body materials: WCC (carbon steel) and CF8M (316 SS)
- Body bolting: A193-B7; nuts: A194-2H; zinc plate (or 304 SS, studs: A193-B8; nuts: A194-8)
- End flanges: integral or separable, 125 RMS raised face flange
- Plug and seat: 316 SS, Alloy 6 overlay and 416 SS
- Trims: full area and reduced
- Bonnet: standard
- Gaskets: PTFE, spiral graphite
- Packing: PTFE V-ring, square graphite, SafeGuard™ Live Loaded, SureGuard™, SureGuard XT™
- Actuator: VL series (aluminum — Buna-N and Viton® O-rings)
- Handwheel: side-mounted and limit stop (25 and 50 VL)
- Positioners: Logix 3220, Logix 3420, Logix 500, XL, Beta
- Accessories: air filter, air filter regulator, coalescing air filter regulator (Valtek or selected boosters)

**Contact Flowserve for additional delivery options.**



Flowserve Corporation  
 5215 North O'Connor Blvd.  
 Suite 2300  
 Irving, Texas 75039-5421 USA  
 Telephone: +1 937 890 5839

Flowserve Corporation has established industry leadership in the design and manufacture of its products. When properly selected, this Flowserve product is designed to perform its intended function safely during its useful life. However, the purchaser or user of Flowserve products should be aware that Flowserve products might be used in numerous applications under a wide variety of industrial service conditions. Although Flowserve can provide general guidelines, it cannot provide specific data and warnings for all possible applications. The purchaser/user must therefore assume the ultimate responsibility for the proper sizing and selection, installation, operation, and maintenance of Flowserve products. The purchaser/user should read and understand the Installation Instructions included with the product, and train its employees and contractors in the safe use of Flowserve products in connection with the specific application.

While the information and specifications contained in this literature are believed to be accurate, they are supplied for informative purposes only and should not be considered certified or as a guarantee of satisfactory results by reliance thereon. Nothing contained herein is to be construed as a warranty or guarantee, express or implied, regarding any matter with respect to this product. Because Flowserve is continually improving and upgrading its product design, the specifications, dimensions and information contained herein are subject to change without notice. Should any question arise concerning these provisions, the purchaser/user should contact Flowserve Corporation at any one of its worldwide operations or offices.

©2019 Flowserve Corporation. All rights reserved. This document contains registered and unregistered trademarks of Flowserve Corporation. Other company, product, or service names may be trademarks or service marks of their respective companies.

VAFLY000032 (EN/AQ) September 2019