

Remove heat and reduce flush fluid temperature to increase mechanical seal reliability and life without cooling water, electricity or compressed air.

The ANC Seal Cooler is designed to increase performance of finned pipe seal cooler designs, including no-wind and low-wind applications. The ANC Seal Cooler can be applied to multiple seal support systems, including piping plans 21, 23, 53B and 53C.

Features and benefits

- Unique conical design maximizes heat transfer in no-wind or low-wind services
- Fully compliant with API 682 4th Edition with large tube size to maximize flow
- 316 stainless steel construction provides superior corrosion resistance
- Minimizes operating costs and maintenance with no utilities required
- Compact design simplifies installation and maintenance, including easy cleaning, venting and draining
- Robust welded fins can be cleaned with power washers
- Two tube lengths with series and parallel flow configurations provide flexibility to achieve the right amount of cooling



Model numbers

Example:		Tube length (m)	Series or parallel coil	Connection type	Flange class
ANC06SW0600	ANC	06	S	W	0600
Model					
06 or 12					
S or P					
N (NPT), T (tube), W (welded flange) or F (flange with tube connector)					
0300, 0600 or 1500					

Add “-P” for Pressure Equipment Directive (PED) 2014/68/EU on 12S and 12P models only.

Note: not all configurations are available on all models.

Technical details for 6 m length

Standard materials of construction	316 stainless steel
Cooling coil tube O.D.	19 mm (0.750 in)
Cooling coil tube wall thickness	2.77 mm (0.109 in)
Effective cooling area	7.3 m ² (78 ft ²)
Maximum temperature	371°C (700°F)
Maximum pressure	200 bar @ 371°C (2,900 psig @ 700°F)
Volume	0.85 or 1.7 L (0.22 or 0.45 gallon)
Connections	Tube end, NPTF or flange
Flange rating	300#, 600# or 1500#



ANC Seal Cooler included in a plan 53B assembly

SSFLY000053-03 (EN/A4) September 2020

Headquarters

Flowserve Corporation
5215 North O'Connor Blvd.
Suite 2300
Irving, Texas 75039-5421 USA
Telephone: +1 937 890 5839

USA and Canada

Kalamazoo, Michigan USA
Telephone: +1 269 381 2650

Europe, Middle East, Africa

Etten-Leur, The Netherlands
Telephone: +31 765 028 200

Asia Pacific

Singapore
Telephone: +65 6544 6800

Latin America

Mexico City
Telephone: +52 55 5567 7170

Flowserve Corporation has established industry leadership in the design and manufacture of its products. When properly selected, this Flowserve product is designed to perform its intended function safely during its useful life. However, the purchaser or user of Flowserve products should be aware that Flowserve products might be used in numerous applications under a wide variety of industrial service conditions. Although Flowserve can provide general guidelines, it cannot provide specific data and warnings for all possible applications. The purchaser/user must therefore assume the ultimate responsibility for the proper sizing and selection, installation, operation, and maintenance of Flowserve products. The purchaser/user should read and understand the Installation Instructions included with the product, and train its employees and contractors in the safe use of Flowserve products in connection with the specific application.

While the information and specifications contained in this literature are believed to be accurate, they are supplied for informative purposes only and should not be considered certified or as a guarantee of satisfactory results by reliance thereon. Nothing contained herein is to be construed as a warranty or guarantee, express or implied, regarding any matter with respect to this product. Because Flowserve is continually improving and upgrading its product design, the specifications, dimensions and information contained herein are subject to change without notice. Should any question arise concerning these provisions, the purchaser/user should contact Flowserve Corporation at any one of its worldwide operations or offices.

©2020 Flowserve Corporation. All rights reserved. This document contains registered and unregistered trademarks of Flowserve Corporation. Other company, product, or service names may be trademarks or service marks of their respective companies.