


Dual seal barrier fluid reservoir

Designed for piping plans 52 and 53A, the 682R series buffer/barrier fluid reservoir provides an ideal supply of clean, cool and reliable working fluid to maximize dual mechanical seal life and reliability.


The Flowserve 682R seal reservoir is compliant with API 682 4th Edition and designed to provide the quickest delivery and most competitive pricing while offering a wide range of popular options. Pre-configured options include elliptical or flanged bottom, pressure and level transmitters or switches, hand pump and stand.

Engineered for reliability and versatility

- Covers a wide operating range with a maximum allowable working pressure (MAWP) of 76.5 bar (1,110 psi) at -40°C to 204°C (-40°F to 400°F)
- Ambidextrous seal connections for optimum piping loop terminations and mounting locations
- Available with NPT or flange (socket welded or butt welded) connection options for easy installation to preferred piping
- Standard 19 liter (5 gallon) reservoir with cooling coils for maximum barrier fluid volume and cooling efficiency
- Pre-configured stand and hand pump options for simplified configuration and reduced lead time
- Designed in accordance with AMSE VIII.1
- Optional U-stamp, CRN and PED (2014/68/EU) available



682R seal reservoir with elliptical bottom



682R seal reservoir with flanged bottom



682R

API 682-compliant seal reservoir

	Model	Size	Configuration	Connections	Pressure Indicator	Instrument Region	Pressure Instrumentation	Level Instrumentation	Reservoir Certification	Option Package	Reservoir Examination
Example: 682R53S1G110B0	682R	5	3	S	1	G	1	1	0	B	0
682R											
19 Liters (5 Gallons) With Cooling Oil, 316/316L SS											
1 Bare Reservoir Elliptical Bottom 2 Bare Reservoir Flanged Bottom 3 Plan 52/53 Assembly Elliptical Bottom 4 Plan 52/53 Assembly Flanged Bottom											
N NPT B BW Flanges S SW Flanges											
0 None 1 0 to 30 psi (0 to 2 bar) 2 0 to 100 psi (0 to 7 bar) 3 0 to 300 psi (0 to 21 bar) 4 0 to 600 psi (0 to 42 bar) 5 0 to 30 psi (0 to 2 bar) With Gage Protector 6 0 to 100 psi (0 to 7 bar) With Gage Protector											
G Global E Europe and Middle East N Americas A Asia Pacific											
See Menu Drawing Available Options.											
See Menu Drawing Available Options.											
0 None C CRN P PED U U-stamp											
0 None H Hand Pump S Squared HSS Stand B Squared HSS Stand and Hand Pump											
0 None 1 LPI 2 PMI 3 LPI+PMI											

SSFLY000438-01 (EN/A4) March 2022

Headquarters

Flowserve Corporation
 5215 North O'Connor Blvd.
 Suite 700
 Irving, Texas 75039-5421 USA
 Telephone: +1 937 890 5839

USA and Canada

Kalamazoo, Michigan USA
 Telephone: +1 269 381 2650

Europe, Middle East, Africa

Etten-Leur, The Netherlands
 Telephone: +31 765 028 200

Asia Pacific

Singapore
 Telephone: +65 6544 6800

Latin America

Mexico City
 Telephone: +52 55 5567 7170

Flowserve Corporation has established industry leadership in the design and manufacture of its products. When properly selected, this Flowserve product is designed to perform its intended function safely during its useful life. However, the purchaser or user of Flowserve products should be aware that Flowserve products might be used in numerous applications under a wide variety of industrial service conditions. Although Flowserve can provide general guidelines, it cannot provide specific data and warnings for all possible applications. The purchaser/user must therefore assume the ultimate responsibility for the proper sizing and selection, installation, operation, and maintenance of Flowserve products. The purchaser/user should read and understand the Installation Instructions included with the product, and train its employees and contractors in the safe use of Flowserve products in connection with the specific application.

While the information and specifications contained in this literature are believed to be accurate, they are supplied for informative purposes only and should not be considered certified or as a guarantee of satisfactory results by reliance thereon. Nothing contained herein is to be construed as a warranty or guarantee, express or implied, regarding any matter with respect to this product. Because Flowserve is continually improving and upgrading its product design, the specifications, dimensions and information contained herein are subject to change without notice. Should any question arise concerning these provisions, the purchaser/user should contact Flowserve Corporation at any one of its worldwide operations or offices.

©2022 Flowserve Corporation. All rights reserved. This document contains registered and unregistered trademarks of Flowserve Corporation. Other company, product, or service names may be trademarks or service marks of their respective companies.